




## CORIO CD-300F Refrigerated/Heating Circulator

**The new generation of laboratory circulators for routine work and standard tasks**

Refrigerated / Heating Circulators of the new CORIO series distinguish themselves with a great price-to-performance ratio. They are ideal for all standard tasks and routine work in laboratories and industry.

### Your advantages

- Models for internal and external applications
- Bright, white, easy to read display
- Very quiet
- Easy pump change-over (internal and external circulation)
- External pump connections (M16x1)
- USB connection
- Space-saving cooling coil design yields more usable space in the bath tank
- Bath lid and drain tap included
- Removable ventilation grid
- Refrigeration unit without side vents
- Class III (FL) according to DIN 12876-1



- Cool-down time (Ethanol)
- Heat-up time (thermal)
- Pump capacity (Water)

### Technical Data

Order No.	9012703
Model series	CORIO
Category	Refrigerated - Heating Circulators
Working temperature range (°C)	-25 ... +150
Temperature control	PID
Temperature stability (°C)	±0.03
Setting / display resolution	0.01 – 0.1 °C
Temperature Display	LED
Heating capacity (kW)	2
Cooling capacity (Medium Ethanol)	°C 20 0 -20 kW 0.31 0.28 0.11
Pump capacity flow rate (l/min)	15
Pump capacity flow pressure (bar)	0.35
Bath opening / bath depth (W x L / D cm)	13 x 15 / 15

Pump connections	M16x1
Barbed fittings diameter (inner dia. / mm)	8 / 12
Filling volume liters	3 ... 4
Refrigerant stage 1	R134a
Filling volume refrigerant stage 1 (g)	100
Global Warming Potential for R134a	1430
Carbon dioxide equivalent stage 1 (t)	0.143
Ambient temperature	5...40 °C
Dimensions W x L x H (cm)	24 x 42 x 66
Weight (kg)	28
Included with each unit	2 each barbed fitting for tubing 8 and 12 mm inner dia. (pump connections M16x1 male)
Bath tank	Stainless steel
Bath cover	integrated
Cooling of compressor	Air
Available voltage versions	230 V / 50 Hz 208 V - 230 V / 60 Hz 115 V / 60 Hz 100 V / 50-60 Hz

## Characteristics



### 100% Checked.

100% testing. 100% quality. Each CORIO undergoes thorough quality testing before leaving the factory.



### More bath.

Designed for more comfort. Thanks to the recessed cooling coil, the internal bath provides more space.



### ATC.

Absolute Temperature Calibration, 1-point calibration (CD).



### Quick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



### Brilliant.

Bright display with strong illumination can be viewed easily from a long distance.



### Safety.

CORIO complies with Class III (FL) according to DIN 12876-1 and switches off automatically in case of high temperature or low liquid level alarm.



### Condensation protection.

Superb design solution. Integrated ventilation directs air over the bath lid and minimizes condensation.



### Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



### Connection. Easy.

Inclined pump connections (M16x1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



### Connectivity.

Remote control made easy. CORIO CP circulators feature a USB connection and RS232 interface.



### Everything at the front.

All operating controls and safety functions are accessed easily and comfortably from the front.



### Exact.

You can rely on it. PID1 control and 'Active Cooling Control' make the new CORIO precise and perfect.



### Green technology.

Development consistently applied environmentally friendly materials and technologies.



### Handle with ease.

Makes day-to-day work easy. Comfortably move your JULABO Circulator around by using the ergonomic handles (front and rear).



### Internal. External.

The pump is controlled via a lever located directly below the display. Easily change between internal and external circulation.




### JULABO. Quality.

Highest standards of quality for a long product life.



### Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at [www.julabo.com](http://www.julabo.com).



### Solid.

Minimized energy loss through high-quality insulation.



### Space saving. Free up space.

Place your JULABO Circulator right next to an application, another unit, or wall. That saves space. This is made possible by eliminating vents and connections on the sides.



### Stable.

Rubber feet allow for a secured footing of your CORIO to prevent damage to your laboratory equipment.



### Switch on. And off you go.

Intelligent operating concept. Ready for operation with just a few quick and easy steps.



### Switch on. And off you go.

Intelligent operating concept. Ready for operation with just a few quick and easy steps.



### Tidy.

The special drain tap for easy draining of bath fluids without tools.



### Touching permitted.

Optimum safety. The ergonomic plastic handle protects your fingers from hot surfaces.



### **Locked in.**

The lockable power plug guarantees safe connection. More process safety.



### **Unique.**

Specially designed pyramids ensure that the condensed liquid drips directly back into the bath.



### **Mobile.**

Extra easy handling. Integrated castors for easy repositioning of refrigerated circulators. (CD-600F, CD-601F, CD-900F, CD-1000F, CD-1001F)



### **USB.**

Remote control made easy. CORIO CD circulators feature a USB connection.