

personal-type, UniFreeze™ system, digital feedback controller, down to -86°C, 82 l



digital feedback controller



IQ | OQ
available
page 12 for details



WUF-25

WUF-25 -86°C, UniFreeze™

Ideal for:

- ultra low refrigeration

Features:

- personal-type compact ultra-low temperature freezer
- freeze down to -86°C
- CFC-free refrigerant
- external temperature sensor hole
- use of block condenser removes filter
- filter-free mechanism lowers compressor heat
- easy maintenance and improved performance
- high-quality insulation panel and inner doors (powder-coated stainless steel) ensure defrosting around outer surface
- stainless steel interior & powder-coated steel body
- CE & RoHS certified and unique serial number for tracing

Safety mechanism:

- built-in standard warning and alarm functions

Controller:

- **digital** feedback controller

Model	WUF-25
Capacity	25 l
Temperature range & sensor	-86°C to -65°C, at 30°C room temperature & 70% humidity, PT 100 sensor
Compressor	Hermetic type
Condenser type	block condenser, no pin, filter free
Shelves	-
Max. rack quantity	none, only 10-15 boxes are applicable
Internal dimensions (W x D x H)	200 x 420 x 300 mm
External dimensions (W x D x H), net weight	390 x 627 x 785 mm, 52 kg
Packing size (W x D x H), gross weight	880 x 860 x 1300 mm, 69 kg
Power supply	1 Phase AC 120V, 60 HZ or AC 230V, 50/60 Hz
Power consumption	321 w/h
Order number 230V	DH.WUF0032
Order number 120V	DH.WUF0132