

FACE  
LIFT

BASIC

★★

EasyTouch



The standard in the laboratory, ideal for a wide range of applications for Industry 4.0

#### Features

- Compatible with school-specific software solutions such as, for example, Vernier® or LabQuest®. Thanks to the KERN School Protocol, as part of technical experiments, weighing data can be transferred to a PC, laptop, etc. for evaluation and display using the USB data interface
- Industry 4.0: The integrated KERN Universal Port (KUP) allows the connection of external KUP interface adapters such as RS-232, USB, Bluetooth, WLAN, Analogue, Ethernet etc. The outstanding advantage here is that the KUP interface adapters are simply plugged in, i.e. retrofitting interfaces is conveniently possible without opening the scale housing or complicated installation. The interface adapters enable convenient transmission of weighing data to networks,

PCs, smartphones, tablets, laptops, printers etc. In addition, control commands and data inputs can also be sent to the scale via the connected devices. Tip: with the KERN KUP-13 extension box, up to three KUP interface adapters can be operated in parallel on the scale.

- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers. for details see page 8/9
- Standardised, simplified concept of operation
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- With the recipe function you can weigh the different ingredients of a mixture. As a check, you can also call up the total weight of all the ingredients

- Weighing with tolerance range (checkweighing): a visual signal helps with portioning, dispensing or grading
- Freely programmable weighing unit, e.g. display direct in special units such as length of thread g/m, paper weight g/m<sup>2</sup>, or similar
- A special Anti-Shock system between the weighing plate and weighing cell reduces vibrations during the weighing process and in this way ensures rapid, reliable weighing results
- Ring-shaped draught shield standard, only for models with weighing plate size , Ø 82 mm, weighing space Ø×H 90×40 mm
- Protective working cover included with delivery




### Technical data

- Backlit LCD display, digit height 21 mm
- Dimensions weighing surface
  - A** Ø 82 mm
  - B** Ø 105 mm
  - C** W×D 130×130 mm
  - D** W×D 150×170 mm, see larger picture
- Weighing plate material
  - A** plastic, with conductive lacquer
  - B**, **C**, **D** stainless steel
- Overall dimensions (without draught shield) W×D×H 163×245×65 mm
- Optional battery operation, 4×1.5 V AA not included in scope of delivery, operating time up to 20 h, AUTO-OFF function to preserve the battery
- Permissible ambient temperature -10 °C/40 °C

### Accessories

- Protective working cover, scope of delivery: 5 items, KERN YBA-A12S05
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01
- External data interface RS-232, Interface cable included, KERN YKUP-01
- External data interface USB, Interface cable included, KERN YKUP-03
- External data interface Ethernet, KERN YKUP-04
- WiFi interface adapter, KERN YKUP-05
- Extension-Box, KERN YKUP-13
- Software BalanceConnection, for flexible recording or transmission of measured values, in particular also to Microsoft® Excel or Access as well as transfer of this data to other Apps and programs, For more details see the internet, Scope of supplies: 1 CD, 1 license, KERN SCD-4.0
- Individual header data: the free software SHM-01 can be used to print 4 header lines on the printout when using printers 911-013, YKN-01, YKB-01N, YKE-01 and YKC-01 (in combination with YKI-02)
- Further details, plenty of further accessories and suitable printers see *Accessories*

#### STANDARD



#### OPTION



Model	Weighing capacity [Max]	Readability [d]	Reproducibility	Linearity	Weighing plate	Option
<b>KERN</b>	<b>g</b>	<b>g</b>	<b>g</b>	<b>g</b>		<b>DAkKS Calibr. Certificate</b>
<b>PCB 200-3</b>	200	0,001	0,001	± 0,005	<b>A</b>	<b>DAkKS</b> KERN 963-127
<b>PCB 300-3</b>	360	0,001	0,001	± 0,005	<b>A</b>	963-127
<b>PCB 300-2</b>	300	0,01	0,01	± 0,02	<b>B</b>	963-127
<b>PCB 1000-2</b>	1000	0,01	0,01	± 0,03	<b>C</b>	963-127
<b>PCB 3000-2</b>	3600	0,01	0,01	± 0,05	<b>C</b>	963-127
<b>PCB 2000-1</b>	2000	0,1	0,1	± 0,2	<b>C</b>	963-127
<b>PCB 6000-1</b>	6000	0,1	0,1	± 0,3	<b>D</b>	963-128
<b>PCB 10000-1</b>	10000	0,1	0,1	± 0,3	<b>D</b>	963-128
<b>PCB 6000-0</b>	6000	1	1	± 2	<b>D</b>	963-128

**Internal adjusting:**

Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)

**Adjusting program CAL:**

For quick setting up of the balance's accuracy. External adjusting weight required

**Easy Touch:**

Suitable for the connection, data transmission and control through PC or tablet.

**Memory:**

Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.

**Alibi memory:**

Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.

**KERN Universal Port (KUP):**

allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort

**Data interface RS-232:**

To connect the balance to a printer, PC or network

**RS-485 data interface:**

To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible

**USB data interface:**

To connect the balance to a printer, PC or other peripherals

**Bluetooth\* data interface:**

To transfer data from the balance to a printer, PC or other peripherals

**WiFi data interface:**

To transfer data from the balance to a printer, PC or other peripherals

**Control outputs (optocoupler, digital I/O):**

To connect relays, signal lamps, valves, etc.

**Analogue interface:**

to connect a suitable peripheral device for analogue processing of the measurements

**Interface for second balance:**

For direct connection of a second balance

**Network interface:**

For connecting the scale to an Ethernet network

**KERN Communication Protocol (KCP):**

It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems

**GLP/ISO log:**

The balance displays weight, date and time, independent of a printer connection

**GLP/ISO log:**

With weight, date and time. Only with KERN printers.

**Piece counting:**

Reference quantities selectable. Display can be switched from piece to weight

**Recipe level A:**

The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out

**Recipe level B:**

Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display

**Totalising level A:**

The weights of similar items can be added together and the total can be printed out

**Percentage determination:**

Determining the deviation in % from the target value (100 %)

**Weighing units:**

Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details

**Weighing with tolerance range:**

(Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model

**Hold function:**

(Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value

**Protection against dust and water splashes IPxx:**

The type of protection is shown in the pictogram.

**Suspended weighing:**

Load support with hook on the underside of the balance

**Battery operation:**

Ready for battery operation. The battery type is specified for each device

**Rechargeable battery pack:**

Rechargeable set

**Universal plug-in power supply:**

with universal input and optional input socket adapters for

- A) EU, CH, GB
- B) EU, CH, GB, USA
- C) EU, CH, GB, USA, AUS

**Plug-in power supply:**

230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available

**Integrated power supply unit:**

Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request

**Weighing principle: Strain gauges**

Electrical resistor on an elastic deforming body

**Weighing principle: Tuning fork**

A resonating body is electromagnetically excited, causing it to oscillate

**Weighing principle: Electromagnetic force compensation**

Coil inside a permanent magnet. For the most accurate weighings

**Weighing principle: Single cell technology:**

Advanced version of the force compensation principle with the highest level of precision

**Verification possible:**

The time required for verification is specified in the pictogram

**DAkkS calibration possible (DKD):**

The time required for DAkkS calibration is shown in days in the pictogram

**Factory calibration (ISO):**

The time required for Factory calibration is shown in days in the pictogram

**Package shipment:**

The time required for internal shipping preparations is shown in days in the pictogram

**Pallet shipment:**

The time required for internal shipping preparations is shown in days in the pictogram