

XS Tester PC 5 - KIT

Code: 50014263



TECHNICAL DATA SHEET

Supplied as standard

Standards applied	
Regulations	CE
Performance	
Accuracy COND	±2 % f. s.
Accuracy (pH)	±0,02
Temperature accuracy	±0,5 °C
Coefficiente di temperatura	0.00 ... 4.00 % / °C
Temperature compensation	Yes % / °C
TDS factor	0.40 ... 1.00
Measuring range COND	0,01 µS ... 199,9 mS
pH measuring range	-2,00 ... 16,00
Salinity measuring range	0,1 mg/l ... 100,0 g/l
TDS measuring range	0,01 mg/l ... 100,0 g/l
temperature measurement range	0,0 ... +60,0 °C
COND Resolution	Scala automatica µS/cm
pH resolution	0.01
Temperature Resolution	0.1 °C
Reference temperature	20,0 ... 25,0 °C
Features	
Display	3-colour backlit LCD
IP rating	67
Calibration points Cond	1 ... 3
PH calibration points	1 ... 3
Swabs recognised Cond	84 µS / 1413 µS / 12,88 mS

Via della Meccanica, 25, 41012 Carpi (MO) - Italy
+39 059 653274 - info@giorgiobormac.com

Recognised pH buffers5 US pads

Feeds

Power supply2 x AAA batteries 1.5 V

Dimensions and weight

Dimensions (WxDxH)40 x 200 mm

Weight0.11 Kg