



## T 10 battery

/// Data Sheet

IKA's first battery-operated, cordless homogeniser. Catered for small volumes up to 100ml (H2O), this homogeniser can even be operated inside of a microcentrifuge tube. The T 10 battery is ideal for on-site sampling operations or use in a biosafety cabinet or laminar flow cabinet due to its compact and portable design and the fact that it does not require an electricity supply in order to operate. It is also ideal as a tissue homogeniser to break down complex tissues. A wide range of dispersing tools are available to suit a variety of application needs such as blunt-edged, sawtooth, stainless steel and plastic types.

Features:





## designed for scientists

- Large TFT display allows for easy parameter viewing
- Brushless DC motor for quieter operation
- Precise speed setting with numerical values
- Timer and counter functions for reproducible and precise operation
- Rechargeable battery with two charging options: Either directly through a USB-C cable or via a charging clamp
- Labworldsoft compatible for remote control and data export and documentation

The dispersing tool is not included in the scope of delivery.

Scope of delivery

•T 10 battery











## designed for scientists

## **Technical Data**

Motor rating input [W]	30	
Motor rating output [W]	25	
Volume range (H2O) [I]	0.0005 - 0.1	
Viscosity max. [mPas]	200	
Speed range [rpm]	8000 - 30000	
Speed deviation [%]	5	
Speed adjustment	stepless	
Speed display	LCD	
Noise without element [dB(A)]	65	
Motor principle	Brushless DC	
Process type	batch	
Power-ON time [min]	10	
Power-OFF time [min]	5	
Timer	yes	
Timer display	LCD	
Dimensions (W x H x D) [mm]	53 x 239 x 70	
Weight [kg]	0.5	
Permissible ambient temperature [°C]	5 - 40	
Permissible relative humidity [%]	80	
USB interface	USB-C	
Power input max. [W]	45	
Power input standby [W]	0.1	
DC Voltage [V=]	15	
Current consumption [mA]	3000	





