













Technical data of syringe filters

Name	Dia. (mm)	Housing material*	Max. operating pressure (psi/bar)	Effective filter area (cm^2)	Hold-up volume after air purging (µl)	Inlet*	Outlet*	Dimensions (mm)
Anotop 10, Anotop 10 Plus, Anotop 10 IC	10	PP	100/6.9	0.78	Anotop 10 & 1C: < 20 Anotop 10 Plus: < 30	FLL	ML	
Anotop 25, Anotop 25 Plus, Anotop 25 IC	25	PP	100/6.9	4.78	Anotop 25 & 1C: < 150 Anotop 25 Plus: < 200	FLL	ML	
GD/X 13	13	PP	100/6.9	1.3	50 (approx)	FLL	ML	
GD/X 25, GD/XP	25	PP	75/5.2	4.6	250 (approx)	FLL	ML	
Puradisc 4 with and without tip (all membranes apart from PVDF)	4	PP	75/5.2	0.2	< 10	FLL	ML	
Puradisc 4 with and without tip (PVDF membrane only)	4	PP	75/5.2	0.2	< 10	FLL	ML Tube Tip	
Puradisc 13	13	PP	75/5.2	1.3	< 25	FLL	ML	
Puradisc 13 with Tube Tip	13	PP	75/5.2	1.3	< 25	FLL	Tube Tip	
Puradisc 25	25	PP	75/5.2	4.2	< 100	FLL	ML	
Puradisc FP	30	PC	100/6.9	5.7	≤ 50	FLL	MLL	
Puradisc FP, Aqua 30	30	PC	100/6.9	5.7	≤ 50	FLL	ML	
ReZist 13, Spartan 13 with Mini-Tip	13	PP	100/6.9	0.75	≤ 10	FLL	Mini-Tip	
ReZist 30	30	PP	100/6.9	5.7	≤ 50	FLL	MLL	
ReZist 30, Spartan 30	30	PP	100/6.9	5.7	≤ 50	FLL	ML	
Roby 25	25	PP	100/6.9	4.2	≤ 50	FLL	ML	
Spartan 13	13	PP	100/6.9	0.75	≤ 10	FLL	ML	

* FLL = Female Luer lock; ML = Male Luer; MLL = Male Luer lock; PP = Polypropylene